



BOXLED® MIDI

■ ■ ■ features + benefits

| | |
|-----------------------|--|
| HOUSING | <ul style="list-style-type: none"> • Die-cast aluminum housing with zinc enriched polyester gray (RAL7040) powder coat. • Chemical, flame and corrosion resistant. • 316 stainless steel latches and hardware. |
| CERTIFICATIONS | <ul style="list-style-type: none"> • Wet location / IP66 / NEMA 4x for integrity and ingress control. • IK09 rated for impact resistance. • 3G rated for vibration resistance. • Title 20 & Title 24 compliant. • Splash Zone 2 sanitation compliant. |
| MOUNTING | <ul style="list-style-type: none"> • Nine (9) mounting configurations allow great flexibility in design. |
| OPERATING TEMPERATURE | <ul style="list-style-type: none"> • Ideal for trying environments. • -30°C to +40°C (-22°F to +104°F). |
| DIMMING | <ul style="list-style-type: none"> • 0-10V Dimming. • Compatible with most dimming systems. |
| ADJUSTABLE OPTICS | <ul style="list-style-type: none"> • Polished aluminum symmetric reflector with field installable asymmetric mod. |
| DIFFUSER | <ul style="list-style-type: none"> • 4mm tempered glass lens provides impact resistance and glare. |
| EXPECTED LED LIFE | <ul style="list-style-type: none"> • L70 rated >60,000. |
| WARRANTY | <ul style="list-style-type: none"> • 5 years. |