

# Special Use Products

## WLX



### Series Features



- Wet Location LED Exit Sign
- Meets NFPA Life Safety 101, NEC, OSHA, Local and State Codes



- Dual-Voltage Transformer for 120/277 VAC Operation



- LED 25+ Years



- Light Grey ABS Housing
- Corrosion Resistant and UV Stabilized
- Polycarbonate Clear Front Cover
- Removable Directional Chevrons
- UL Listed

## 2EWLX



### Additional Emergency Unit Features



- Integrated Solid State System
- Brownout Sensitivity
- AC Lockout



- 2EWLX:(2) 7 W Adjustable Lamp Heads
- Optional 1.5W LED Bulb



- Sealed Nickel Cadmium 6V
- Maintenance Free



- Sealed Momentary Test Switch
- Sealed AC Ready Light
- Wall-mount only

### Ordering Information

WLX	1	R
WLX - AC Only	# Faces	Letter Color
EWLX - Battery & Backup	1	<u>R</u> ed
2EWLX-Emer. Exit Combo		<u>G</u> reen

### Dimensions

#### WLX

Height: 12.0"  
Width: 12.0"  
Depth: 3.75"

#### 2EWLX

Height: 18.0"  
Width: 12.0"  
Depth: 3.75"

HTR- Heater

For wet and corrosive environments. A heavy-duty gasket protected housing makes the enclosure resistant to corrosive atmospheres, non-hazardous dust, water spray, splash and even hose-downs. Ideal for industrial or other applications subject to wet or cold weather.



UL 924 LISTED