







Series Features

	<ul style="list-style-type: none"> • 120/277 VAC Operation • Maximum Input Rating (120 or 277VAC) <ul style="list-style-type: none"> Single Face 3.6 Watts Double Face 5.6 Watts
	<ul style="list-style-type: none"> • Light-Emitting Diodes – 25+ Year Life • Illuminates with Uniform Color and Brightness • 100–300 Foot Visibility
	<ul style="list-style-type: none"> • Ceiling, End or Back Mount • Canopy • 20-Gauge Steel Housing • Acrylic Shield • White Powder-Coat Finish • Universal Directional Chevrons • UL Listed

Additional Emergency Unit Features

	<ul style="list-style-type: none"> • Maximum Input Rating (120 or 277VAC) <ul style="list-style-type: none"> Single Face 6.8 Watts Double Face 8.0 Watts • Integrated Solid State System • Constant Current, Controlled Automatic Charger Circuit • Low-Voltage Battery Cutoff • Brownout Sensitivity • Voltage Surge Protection
	<ul style="list-style-type: none"> • Sealed Nickel Cadmium Battery • 5-Year Shelf Life • 10-Year Battery Warranty • Maintenance-Free
	<ul style="list-style-type: none"> • 3+ Hours Illumination (Single Face) in DC Mode • 1.5+ Hours Illumination (Double Face) in DC Mode • Test Switch • Amber (AC On/Charger Operation) Indicator

Ordering Information

EXFLD	1	R	W	W	-FAI
Series	# Faces	Letter Color	Stencil Color	Housing Color	Options
XFLD – AC Only	1	Red	White*	White*	Factory Options
EXFLD – Emer.	2	Green	Black PM Painted Matte Chrome	Black PM Painted Matte Chrome	

XFLD



Accessories

- Order Separately
- 63 Wire Guard (for Single-Face Back Mount Only)
 - P12W 12" Pendant Kit, White*
 - P12B 12" Pendant Kit, Black*
 - *Pendant Kits from 12" to 84" Available
 - VDS Vandal-Deterrent Shield (for Single-Face Back Mount Only)

Dimensions

XFLD/EXFLD
 Height: 7.7"
 Width: 12.5"
 Depth: 2.7"

Options

Add Suffix to Catalog Number

- BZ Audible Buzzer in Emergency Mode (EXFLD Only)
- DL Downlight LED
- FAI Fire Alarm Interface
- FL Flasher in Emergency Mode (EXFLD Only)
- HI High-Intensity LEDs
- REC Recessed Housing (Single Face Only)
- TP Tamper-Proof Screws

Master/Slave Options:

- SL Slave (Requires Single-Face EXFLD as Power Source)
- REC/S Recessed Mounting for Slave Only
- REC/M Recessed Mounting for Master Only
- REC/MS Recessed Mounting for Master and Slave



Made in USA